

SPRAY GUN NOZZLE RECOMMENDATIONS



Smart Look. Smart Choice.



National Rule Products	LPH	W400LV	LPH400LV	LPH400LVX	SUPERNOVA LS40002	SUPERNOVA WS40002
Primers						
Wanda 8100 2K Primer	Nozzle Size Air Pressure	2.0 mm psi				
Primer Surfacer						
Wanda 8100 2K Primer	Nozzle Size Air Pressure	1.6 mm psi				
Primer Sealer						
Wanda Non Sand Sealer	Nozzle Size Air Pressure	1.6 mm psi				
Wanda Plastic Primer	Nozzle Size Air Pressure	1.4 mm psi				
Low VOC Primer						
Wanda Low VOC Primer	Nozzle Size Air Pressure	1.6 mm psi				
Low VOC Sealer						
Wanda Low VOC Sealer	Nozzle Size Air Pressure	1.6 mm psi				
Single Stage						
Wanda PU	Nozzle Size Air Pressure		1.4 mm 16 psi	1.4 mm 16 psi	1.4 mm 2 psi	
Basecoat						
Wandabase HS	Nozzle Size Air Pressure		1.4 mm 16 psi	1.4 mm 16 psi	1.4 mm 2 psi	
Waterborne Basecoat						
Wanda Waterbase	Nozzle Size Air Pressure		1.4 mm 20 psi	1.4 mm 16 psi	1.4 mm 16 psi	1.4 mm 2 psi
						1.4 mm 29 psi
Clearcoat						
Wanda 8100 Clearcoat	Nozzle Size Air Pressure		1.4 mm 20 psi	1.4 mm 16 psi	1.4 mm 2 psi	1.4 mm 29 psi
Wanda Low VOC Clearcoat	Nozzle Size Air Pressure		1.4 mm 20 psi	1.4 mm 16 psi	1.4 mm 2psi	1.4 mm 29 psi

These recommendations are based on reliable research.

Experimentation may be required with multiple fluid nozzle recommendations, to best suit your application technique.
 Referenced air pressure data in this chart are all measured with full trigger.
 The recommended air pressure must be set with a full trigger condition on the spray gun.

All trademarks are the property of their respective owners.
 © 201 ANEST IWATA USA, Inc.